

como

True Quality is an Experience

mountain
luxury vinyl

Technical Data Como Mountain LVT

Material:	LVT 3mm (0.55 wear layer)
Dimensions:	229 x 1219mm 14pcs/ctn, 56ctn/pallet, 3.90sqm
Weight per Box:	22.9kg
Weight per Pallet:	1282kg

Characteristics	Testing Procedure	Results
Wearlayer	EN 429	PASS
Usage category	RESIDENTIAL, COMMERCIAL	
Overall thickness	EN 428	PASS
Total weight / m3	EN 430	PASS
Anti static	EN1081	app 10 ¹¹ Ohm
Dimension square - and straightness	ASTM F2199	0.07%-0.13%
Height difference	ISO23999	0mm
Dimensional stability	ASTM F2199	less than 0.020"/ft
Colour fastness to artificial light	ISO 105-B02	m>6 Grade
Resistance to chemical products	ASTM F925	PASS
Toxic element test	Floorscore	ND
Castor chair	NALFA	PASS
Flexibility	EN435	Pass
Impact resistance	EN433	Pass
Reaction to fire	EN13501	Bfl-S1
Slip resistance	ASTM D 2047	>0.6
Thermal conductivity Suitable for underfloor heating	DIN 52612	0.02m ² k/w
Abration resistance	EN649	T
Sound reduction	ASTM90	STC 58 db
Emission of formaldehyd	Floorscore	ND



GLOBAL STREAM
IMPORT EXPORT
Imported and distributed by



FIND US ON
SOCIAL MEDIA



SCAN ME
TO VISIT OUR
WEBSITE
www.globalstream.co.za